



MP110E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 50Hz						
400V	KVA		KW			
Prime	100.0		80.0			
Standby	110.0		88.0			
			@ 0.8 p.f.			
Generator Outp	out Rating	at - 60H	lz			
480V	KVA		KW			
Prime	114.4		91.5			
Standby	126.5		101.2			
			@ 0.8 p.f.			
Engine Data						
Engine Manufact			Perkins UK			
Linginie ivianiulaci	urer:	Perki	ns UK			
Engine Model:	urer:		ns UK 44TAG2			
		1104C-				
Engine Model:	lers:	1104C-	44TAG2			
Engine Model: Number of Cylind	lers:	1104C-	44TAG2 1			
Engine Model: Number of Cylind Cylinder Arrange	lers: ment:	1104C- Vertica 4 St	44TAG2 4 I In Line			
Engine Model: Number of Cylind Cylinder Arranger Cycle:	lers: ment: (in): 105	1104C- Vertica 4 St 5.0 (4.1) 2	44TAG2 4 I In Line roke			
Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	lers: ment: (in): 109	Vertica 4 St 5.0 (4.1) a cocharge	44TAG2 I In Line roke 127.0 (5.0) d & air-to-air			

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	220.0	58.1		
Fuel Tank:	UV Resistant MDPE			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Performance	50Hz		60	60HZ	
Engine Speed:	1500		18	00	
Gross Engine Power:	kWm	Bhp	kWm	Bhp	
Prime:	93.6	125.5	106.8	143.1	
Standby:	103.0	138.1	117.5	157.6	
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr	
Prime:	22.6	5.97	26.9	7.106	
Standby:	24.9	6.578	29.7	7.846	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wid	dth	He	ight	[Ory	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2200.0	86.6	746.0	29.9	1465.0	57.7	1123.0	2475.8	1150.0	2535.3

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	6.27	221	7.8	275
Exhaust Gas Flow:	16.3	576	20.4	720
Radiator Cooling: Air Flow	165.6	5848	225.6	7967

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer	: Leroy Somer
Alternator Model:	LSA44.3 S5 TALO44D
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 5%
Wires:	12 6
Ingress Protection Rating	: IP 23
Excitation System:	Shunt
Excitation System:	Shunt



Winding Pitch Code:

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

2/3 - 6



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	12.6	3.3	12.6	3.3
Lube Oil Capacity:	8.0	2.1	8.0	2.1
	°C	°F	°C	°F
Exhaust Temperature:	543	1009	574	1065



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



0407/2017