



MP150E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating at	- 50Hz
400V	KVA	KW
Prime	135.0	108.0
Standby	150.0	120.0
		@ 0.8 p.f.
Generator Outp	out Rating at	- 60Hz
480V	KVA	KW
Prime	152.0	122.0
Standby	169.0	135.0
		@ 0.8 p.f.
Engine Data		
Engine Manufact	urer:	Perkins UK
Engine Manufact Engine Model:		Perkins UK 106A-70TG1
	1	
Engine Model:	1 lers:	106A-70TG1
Engine Model: Number of Cylind	1 lers:	106A-70TG1 6
Engine Model: Number of Cylind Cylinder Arrangel	lers: ment: V	.106A-70TG1 6 ertical In Line
Engine Model: Number of Cylind Cylinder Arranger Cycle:	1 lers: ment: V (in): 105.0 Turbo c	106A-70TG1 6 ertical In Line 4 Stroke
Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	1 lers: ment: V (in): 105.0 Turbo c	106A-70TG1 6 ertical In Line 4 Stroke (4.1) x 135.0 (5.3) charged & air-to-air

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	400.0	105.7		
Fuel Tank:	Powder Co	ated Steel		
Base Frame:	Heavy Duty-Po	owder Coated		
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Po	ole MCB		

800
Bhp
188.0
208.0
US Gal/Hr
9.298
10.24

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wi	dth	He	eight	I	Dry	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2683.0	105.6	1000.0	39.4	1670.0	65.7	1725.0	3803.0	1748.0	3845.0

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz
	M³/min Ft³/n	nin M³/min Ft³/mir
Combustion Air Flow:	8.09 286	5 11.86 419
Exhaust Gas Flow:	22.66 800	29.72 1049.5
Radiator Cooling: Air Flow	182 642	7 182 6427

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacture	er: Leroy Somer
Alternator Model:	LSA44.3 M8 TALO44H
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion	on: < 5%
Wires:	12 6
Ingress Protection Rating	g: IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication 50Hz 60Hz US/Gal US/Gal Liter Coolant Capacity: 21.0 5.5 21.0 5.5 Lube Oil Capacity: 18.0 4.7 18.0 4.7 °C °F °C °F Exhaust Temperature: 576 1069 526 979



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



7-2015 REV.1