

MP16E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Concreter Outr	t Detine	ot E	NU_
Generator Outp	but Rating	at - 5	JHZ
400V	KVA		KW
Prime	15.0		12.0
Standby	16.5		13.2
			@ 0.8 p.f.
Generator Outp	out Rating	at - 6)Hz
480V	KVA		KW
Prime	N/A		N/A
Standby	N/A		N/A
			@ 0.8 p.f.
Engine Data			
Engine Manufact	urer:	Per	kins UK
<u> </u>	urer:		kins UK A-15G2
Engine Manufact			
Engine Manufact Engine Model:	lers:	403	A-15G2
Engine Manufact Engine Model: Number of Cyline	lers:	403 Vertic	A-15G2 3
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	lers: ment:	403 Vertic	A-15G2 3 cal In Line
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle:	ders: ment: (in): 8 [,]	403 Vertio 4 1 4.0 (3.3	A-15G2 3 cal In Line Stroke
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	lers: ment: (in): 8 [,]	403 Vertio 4 1 4.0 (3.3 Vatural	A-15G2 3 cal In Line Stroke) x 90.0 (3.5)

General Data

	Liter	US/Gal			
Fuel Tank Capacity:	100.0	26.4			
Fuel Tank:	UV Resistant MDPE				
Base Frame:	Heavy Duty-Powder Coated				
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Pole MCB				

Performance	nce 50Hz		60HZ	
Engine Speed:	150	1500		800
Gross Engine Power:	kWm	kWm Bhp		Bhp
Prime:	14.0	18.0	N/A	N/A
Standby:	15.4	20.7	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	4.1	1.08	N/A	N/A
Standby:	4.9	1.29	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Length Width Height Dry							Wet		
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
1325.0	52.2	720.0	28.3	1185.0	46.7	452.0	996.5	460.0	1014.1
* With Lube Oil * With Lube Oil & Coolant									

Rating Definition

Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³⁄min	Ft³/min	M³∕min	Ft³∕min
Combustion Air Flow:	1.10	35	N/A	N/A
Exhaust Gas Flow:	2.9	77.7	N/A	N/A
Radiator Cooling: Air Flow	41.4	1462	N/A	N/A

*Cooling system designed to operate in high ambient conditions

_			
	ternat	0.17	
/ <u> </u>		[0]	
_	CO I I I OI		

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 40 S3 TAL040D
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 4% < 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	6.0	1.6	N/A	N/A
Lube Oil Capacity:	6.0	1.6	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	470	878	N/A	N/A

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



JAN2014 VER.1

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com