



MP200E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output F	Rating at -	50Hz		
400V	KVA		KW	
Prime	180.0		160.0	
Standby	200.0		176.0	
			@ 0.8 p.f.	
Generator Output F	Rating at -	60Hz		
480V	KVA		KW	
Prime	168.8		135.0	
Standby	187.5		150.0	
			@ 0.8 p.f.	
Engine Data				
Engine Manufacturer:	Pe	rkins l	JK	
Engine Model:	1106	6A-70T	AG3	
Number of Culindons				
Number of Cylinders:		6		
Cylinder Arrangement	: Vert	6 ical In	Line	
-				
Cylinder Arrangement		ical In Strok	9	
Cylinder Arrangement Cycle:	105.0 (4. Turbo cha	ical In Stroke 1) / 13	e 5.0 (5.3) a air-to-air	
Cylinder Arrangement Cycle: Bore/Stroke mm (in):	105.0 (4. Turbo cha	ical In Stroke 1) / 13 rged 8	e 5.0 (5.3) a air-to-air	

General Data					
	Liter	US/Gal			
Fuel Tank Capacity:	400.0	116.2			
Fuel Tank:	Powder Co	Powder Coated Steel			
Base Frame:	Heavy Duty-Powder Coated				
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Po	ABB 3 Pole MCB			

Engine Speed: 1500 1800 Gross Engine Power: kWm Bhp kWm Bhp Prime: 162.7 218.2 155.4 208.4 Standby: 180.2 241.7 171.8 230.4 Fuel Consumption: L/Hr Us Gal/Hr L/Hr Us Gal/Hr
Prime: 162.7 218.2 155.4 208.4 Standby: 180.2 241.7 171.8 230.4
Standby: 180.2 241.7 171.8 230.4
Fuel Consumption: L/Hr us Gal/Hr L/Hr us Gal/Hr
Prime: 41.4 10.9 38.2 10.1
Standby: 45.1 11.9 41.7 11.0

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wie	dth	He	eight	I	Ory	,	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2903.0	114.3	1000.0	39.4	1770.0	69.7	1820.0	4012.4	1878.0	4140.0

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz		
	M³/min Ft³/min	M³/min Ft³/min		
Combustion Air Flow:	13.2 466.1	16.37 N/A		
Exhaust Gas Flow:	36.8 1299.5	38.35 N/A		
Radiator Cooling: Air Flow	222.0 7840	282 N/A		

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Leroy Somer
LSA 46.3 S2 TALO46A
Single (1)
Н
< 2.5% < 5%
12 6
IP 23
Shunt
2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication 50Hz 60Hz Liter US/Gal US/Gal Coolant Capacity: 21.0 5.55 20.5 5.42 Lube Oil Capacity: 18.0 4.75 18.0 4.75 °C °F °C °F Exhaust Temperature: 765 491 915 407



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



7-2015 REV.1