



# MP1880E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	ut Rating at -	50Hz				
400V	KVA	KW				
Prime	1710.0	1368.0				
Standby	1880.0	1504.0				
		@ 0.8 p.f.				
Generator Output Rating at - 60Hz						
480V	KVA	KW				
Prime	N/A	N/A				
Standby	N/A	N/A				
		@ 0.8 p.f.				
Engine Data						
Engine Manufactu	rer: Pe	Perkins UK				
Engine Model:		2-46TAG3A				
Engine Model: Number of Cylinde	401					
•	401 ers:	2-46TAG3A				
Number of Cylinde	401 ers: nent:	2-46TAG3A 12				
Number of Cylinde Cylinder Arrangen	401 ers: nent:	2-46TAG3A 12 60 Vee				
Number of Cylinde Cylinder Arrangen Cycle:	401 ers: nent: in): 160.0 (6 Turbo cha	2-46TAG3A 12 60 Vee 4 Stroke				
Number of Cylinder Cylinder Arrangen Cycle: Bore/Stroke mm (i	401 ers: in): 160.0 (6 Turbo cha cha	2-46TAG3A 12 60 Vee 4 Stroke .3) / 190.0 (7.5) arged & air to air				

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	N/A	N/A		
Fuel Tank:	N/A			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Performance	50	50Hz		HZ
Engine Speed:	150	1500		800
Gross Engine Power:	kWm	kWm Bhp		Bhp
Prime:	1500.0	2012.0	N/A	N/A
Standby:	1643.0	2203.0	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	370.0	97.7	N/A	N/A
Standby:	405.0	107.0	N/A	N/A

## **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Length Width Height				Dry		Wet			
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5300.0	280.7	2200.0	87.0	2680.0	105.6	10890	24008	11095	24460
	* With Lube Oil				* With Lube Oi	l & Coolant			

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

## **Rating Definition**

# Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

# Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz		
	M∛min	M³∕min Ft³/min		M³/min Ft³/min	
Combustion Air Flow:	135.0	4768	N/A	N/A	
Exhaust Gas Flow:	350.0	12360	N/A	N/A	
Radiator Cooling: Air Flow	2220.0	78399	N/A	N/A	

\*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 S5
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 4%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - 6S



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

<b>Cooling &amp; Lubrication</b>	50	)Hz	6(	)Hz	
	Liter	US/Gal	Liter	US/Gal	
Coolant Capacity:	210.0	55.5	N/A	N/A	
Lube Oil Capacity:	177.0	46.8	N/A	N/A	
	°C	°F	°C	°F	
Exhaust Temperature:	480	896	N/A	N/A	



### **Other Information**

### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

### Distributed & Serviced by:



JAN2014 VER.1

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com