



MP220E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output F	Rating at -	50H	z	
400V	KVA		KW	
Prime	200.0		160.0	
Standby	220.0		176.0	
			@ 0.8 p.f.	
Generator Output F	Rating at -	60H	lz	
480V	KVA		KW	
Prime	N/A		N/A	
Standby	N/A		N/A	
			@ 0.8 p.f.	
Engine Data				
Engine Manufacturer:	Pe	rkins	UK	
Engine Manufacturer: Engine Model:			UK DTAG4	
Engine Model:	1106	6 6		
Engine Model: Number of Cylinders:	1106 :: Vert	6 6	n Line	
Engine Model: Number of Cylinders: Cylinder Arrangement	1106 :: Vert	6 6 ical II	n Line	
Engine Model: Number of Cylinders: Cylinder Arrangement Cycle:	1106 :: Vert 4 105.0 (4. Turbo cha	6 ical III Stro 1) / 1	n Line ke	
Engine Model: Number of Cylinders: Cylinder Arrangement Cycle: Bore/Stroke mm (in):	1106 :: Vert 4 105.0 (4. Turbo cha Cha	6 ical III Stro 1) / 1	n Line ke 135.0 (5.3) & air-to-air	

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	400.0	116.2	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

Performance	50Hz		60HZ	
Engine Speed:	15	1500		800
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	178.9	240.0	N/A	N/A
Standby:	196.3	263.2	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	45.8	12.1	N/A	N/A
Standby:	49.4	13.1	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wid	lth	He	ight	[Dry	\	Net
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2903.0	114.3	1000.0	39.4	1770.0	69.7	1820.0	4012.4	1878.0	4140.0

* With Lube Oil & Coolant

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz
	M³/min Ft³/min	M³/min Ft³/min
Combustion Air Flow:	13.2 466.1	N/A N/A
Exhaust Gas Flow:	36.8 1299.5	N/A N/A
Radiator Cooling: Air Flow	222.0 7840	N/A N/A

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 S3 TAL046B
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 2 % <i><</i> 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication 50Hz 60Hz Liter US/Gal US/Gal Coolant Capacity: 21.0 5.54 N/A N/A Lube Oil Capacity: 4.75 18.0 N/A N/A °C °F °C °F Exhaust Temperature: 550 1022 N/A N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



7-2015 REV.1