



MP2250E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Rating a	at - 50Hz	
400V	KVA		KW
Prime	2000.0		1600.0
Standby	2250.0		1800.0
			@ 0.8 p.f.
Generator Out	out Rating a	at - 60Hz	:
480V	KVA		KW
Prime	N/A		N/A
Standby	N/A		N/A
			@ 0.8 p.f.
Engine Data			
Engine Data Engine Manufact	urer:	Perkins	s UK
	urer:	Perkins 4016-61	••••
Engine Manufact			••••
Engine Manufact Engine Model:	lers:	4016-61	TRG2
Engine Manufact Engine Model: Number of Cyline	lers:	4016-61 16	TRG2
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	lers: ment:	4016-61 16 60° V 4 Stro	TRG2
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle:	lers: ment:	4016-61 16 60° V 4 Stro	TRG2 ee ke .3) x (7.5)
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	lers: ment: <i>(in):</i> 160	4016-61 16 60° V 4 Strc 0 x 190 (6	TRG2 ee ke .3) x (7.5) arged

General Data

	Liter	US/Gal		
Fuel Tank Capacity:	N/A	N/A		
Fuel Tank:	N/A			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole ACB			

*Breaker supplied loose in a standalone cabinet on open type generating sets

Performance	50Hz		60HZ	
Engine Speed:	1500		1800	
Gross Engine Power:	kWb	Bhp	kWm	Bhp
Prime:	1774	2378.9	N/A	N/A
Standby:	1985	2662	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	405	107.0	N/A	N/A
Standby:	463	122.3	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights Dry Width Wet Length Height Millimeter Millimeter Inch Inch Millimeter KG LB KG LB Inch * With Lube Oil * With Lube Oil & Coolant

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

Rating Definition

Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³∕min	Ft³∕min	M∛min	Ft³∕min
Combustion Air Flow:	175	6180	N/A	N/A
Exhaust Gas Flow:	475	16775	N/A	N/A
Radiator Cooling: Air Flow	2820	99587	N/A	N/A

*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 L9
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 4%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	50	50Hz)Hz
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	552	145.8	N/A	N/A
Lube Oil Capacity:	213.0	56.5	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	488	910	N/A	N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com