



MP2500E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 50Hz						
400V	KVA		KW			
Prime	2250		1800.0			
Standby	2500		2000.0			
			@ 0.8 p.f.			
Generator Ou	ıtput Ratin	g at - 60Hz				
480V	KVA		KW			
Prime	N/A		N/A			
Standby	N/A		N/A			
			@ 0.8 p.f.			
Engine Data						
Engine Manuf	facturer:	Perkin	s UK			
Engine Model:		4016-61TRG3				
Number of Cylinders:		16				
Cylinder Arrangement:		60° Vee				
Cycle:		4 Stroke,				
Bore/Stroke mm (in):		160 x 190 (6.3) x (7.5)				
Induction:		Turbocharged				
Compression ratio:		13:1 nominal				
Displacement	I (cu.in):	61.123 ((3729)			

General Data						
		Liter	•	US/Gal		
Fuel Tank Capacity:		N/A		N/	Ά	
Fuel Tank:			N/A			
Base Frame:	Heavy Duty-Powder Coated				d	
Control Panel:	Deep Sea Electronics					
Circuit Breaker:	Circuit Breaker: ABB 3 Pole ACB					
*Breaker supplied loose in a standalone cabinet on open type generating sets						
Performance		5	0Hz	60	OHz	
Performance Engine Speed:		5 0			OHz 00	
Engine Speed:		15	00	18	00	
Engine Speed: Gross Engine Power	1	15 kWm	00 <i>Bhp</i>	18	00 <i>Bhp</i>	
Engine Speed: Gross Engine Power Prime:	2	15 kWm .975.0	00 Bhp 2648.5	18 <i>kWm</i> N/A	00 <i>Bhp</i> N/A	

Standard Reference Conditions:

Standby:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

529

139.7

N/A

N/A

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Width Height		[Dry	Wet			
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5803	228.4	2225	87.5	3930	154.7			15700	34612.5
	* With		* With Lube (Dil	* With Lube Oi	I & Coolant			

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50 Hz		60	60 Hz	
	M ³ /min	Ft³/min	M³/min	Ft³/min	
Combustion Air Flow:	175.0	6180	N/A	N/A	
Exhaust Gas Flow:	525.0	18540	N/A	N/A	
Radiator Cooling Air Flow:	3320.0	117245	N/A	N/A	

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 L9
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 4%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - n° 6S

Principles

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability.

MARAPCO incorporates this engine throughout their full range.

Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.

Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Cooling & Lubrication	1 - E	50 Hz	(60 Hz		
	Liter	US/Gal	Liter	US/Gal		
Coolant Capacity:	500.0	132.1	N/A	N/A		
Lube Oil Capacity:	213.0	56.2	N/A	N/A		
	°C	°F	°C	°F		
Exhaust Temperature:	560	1040	N/A	N/A		



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are Registered Trademarks

0407/2017