

MP275E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating at	t - 50Hz
400V	KVA	KW
Prime	250.0	200.0
Standby	275.0	220.0
		@ 0.8 p.f.
Generator Outp	out Rating at	t - 60Hz
480V	KVA	KW
Prime	225.0	180.0
Standby	250.0	200
		@ 0.8 p.f.
Engine Data		
Engine Manufact	urer:	Perkins UK
_		Perkins UK 06A-E70TTAG3
Engine Manufact	12	
Engine Manufact Engine Model:	12 lers:	06A-E70TTAG3
Engine Manufact Engine Model: Number of Cylind	12 lers:	06A-E70TTAG3
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange	12 ders: ment: V	06A-E70TTAG3 6 /ertical In Line
Engine Manufact Engine Model: Number of Cylind Cylinder Arranger Cycle:	12 ders: ment: V (in): 105 Twin	6 /ertical In Line 4 Stroke
Engine Manufact Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	ders: ment: V (in): 105 Twin	6 /ertical In Line 4 Stroke (4.1) x 135 (5.3) turbo & air-to-air

General Data					
	Liter	US/Gal			
Fuel Tank Capacity:	600	158.5			
Fuel Tank:	Powder Coated Steel				
Base Frame:	Heavy Duty-Powder Coated				
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Po	le MCCB			

Performance	50Hz 60HZ		HZ	
Engine Speed:	15	1500		00
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	226.2	303.3	217.0	291
Standby:	248.6	333.4	239.6	321.3
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	56.9	15.0	54.5	14.4
Standby:	64.5	17.0	61.1	16.1

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wic	dth	He	ight	ı	Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3500.0	137.8	1096.0	43.1	1820.0	71.6	2435.0	5368.2	2465.0	5434.4

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min F	t³/min	M³/min	Ft³/min
Combustion Air Flow:	15.7	554	14.0	494
Exhaust Gas Flow:	33.66 1	1189	31.18	1101
Radiator Cooling: Air Flow	265.2 1	3066	337.2	17022

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 S5 TAL046D
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 2.5% < 5%
Wires:	12 6
Ingress Protection Rating:	IP23
Excitation System:	Shunt
Winding Pitch Code:	2/3 (n° 6)



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	5	50Hz		OHz
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	25	6.6	25	6.6
Lube Oil Capacity:	16	4.2	16	4.2
	°C	°F	°C	°F
Exhaust Temperature:	511	952	505	941

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



2103/2016