



MP34-MP37.5E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 60Hz				
220/127 V	KVA	KW		
Prime	34.0	27.0		
Standby	37.5	30.0		
		@ 0.8 p.f.		
Generator Outp	out Rating at	: - 60Hz		
380/220V	KVA	KW		
Prime	30.0	24.0		
Standby	33.0	26.5		
		@ 0.8 p.f.		
Engine Data				
Engine Manufact	urer:	Perkins UK		
Engine Model:		1103A-33G		
Number of Cylind	ders:	3		
Cylinder Arrange	ment: V	ertical In Line		
Cycle:		4 Stroke		
Bore/Stroke mm	(in): 105.0	(4.1) / 127.0 (5.0)		
Induction:	Nat	urally Aspirated		
Compression rati	o:	19.25:1		
Displacement / (c	ru.in):	3.3 (201.4)		

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	220.0	58.1	
Fuel Tank:	UV Resistant MDPE		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

Performance	60	HZ
Engine Speed:	18	00
Gross Engine Power:	kWm	Bhp
Prime:	33.2	44.5
Standby:	36.5	48.9
Fuel Consumption:	L/Hr	US Gal/Hr
Prime:	8.6	2.27
Standby:	9.5	2.51

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

		11.00		10.0
imens	ione a	nd V	VAIA	hte
		I I I A MA	MEILO	

Len	gth	Wid	dth	He	ight	0	Dry	'	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
1828.0	72.0	790.0	31.1	1465.0	57.7	689.0	1519.0	710.0	1565.3
						* With Lube Oil		* With Lube Oil	& Coolant

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	60Hz		
	M³/min	Ft³/min	
Combustion Air Flow:	2.57	90.7	
Exhaust Gas Flow:	6.6	233	
Radiator Cooling: Air Flow	70.2	2472	

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA42.3VS2
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	at no load <3%
Wires:	12
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	60	60Hz		
	Liter	US/Gal		
Coolant Capacity:	10.2	2.7		
Lube Oil Capacity:	7.9	2.1		
	°C	°F		
Exhaust Temperature:	530	986		



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories, all data is correct at the time of processing and we reserve the right to change specification without prior notice

Distributed & Serviced by:



2104/2020