



MP400E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outpu	ıt Rating at	- 50Hz	
400V	KVA	KW	/
Prime	350.0	280	.0
Standby	400.0	320	.0
,	100.0	3.23	0.8 p.f.
Generator Outpu	ıt Rating at		•
480V	KVA	КИ	/
Prime	400.0	320	.0
Standby	438.0	350	
	430.0		0.8 p.f.
Eurius Data			
Engine Data			
Engine Data Engine Manufactur	rer:	Perkins USA	
		Perkins USA 06A-E13TAG2	
Engine Manufactur	22		
Engine Manufactur Engine Model:	22 rs:	06A-E13TAG2	
Engine Manufactur Engine Model: Number of Cylinde	22 rs:	06A-E13TAG2	
Engine Manufactur Engine Model: Number of Cylinde Cylinder Arrangem	rs: ent: Vo	06A-E13TAG2 6 ertical In Line	1)
Engine Manufactur Engine Model: Number of Cylinde Cylinder Arrangem Cycle:	22 rs: ent: Vo n): 130.0 Turbo c	06A-E13TAG2 6 ertical In Line 4 Stroke	•
Engine Manufactur Engine Model: Number of Cylinde Cylinder Arrangem Cycle: Bore/Stroke mm (in	22 rs: ent: Vo n): 130.0 Turbo c	06A-E13TAG2 6 ertical In Line 4 Stroke (5.1) / 157.0 (6.	•

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	800.0	211.3		
Fuel Tank:	Powder Coated Steel			
Base Frame:	Heavy Duty-Po	owder Coated		
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

10	
1800	
wm	Bhp
373.4	500.7
06.5	545.1
L/Hr	US Gal/Hr
81	21.4
87	22.98
	373.4 106.5 L/Hr

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wic	lth	He	ight	[Dry	,	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3575.0	140.7	1120.0	44.1	2137.0	84.1	3220.0	7098.9	3320.0	7319.3

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	23.6	833	29.0	1024
Exhaust Gas Flow:	64.8	2288	73.5	2596
Radiator Cooling: Air Flow	654.0	23096	788.0	27828

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 L11 TAL046H
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 2.5% < 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	51.4	13.6	51.4	13.6
Lube Oil Capacity:	40.0	10.6	40.0	10.6
	°C	°F	°C	°F
Exhaust Temperature:	630	1166	660	1220



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



JAN2014 VER.1