



MP513-MP563E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	put Rating a	t - 60Hz			
220/127v	KVA	KW			
Prime	513.0	410.4			
Standby	563.0	450.4			
		@ 0.8 p.f.			
Generator Output Rating at - 60Hz					
380/220V	KVA	KW			
Prime	475	380			
Standby	527	422			
		@ 0.8 p.f.			
Engine Data					
Engine Data Engine Manufact	urer:	Perkins Seguin			
		Perkins Seguin 506A-E15TAG3			
Engine Manufact	2	U			
Engine Manufact Engine Model:	2 ders:	506A-E15TAG3			
Engine Manufact Engine Model: Number of Cyline	2 ders:	506A-E15TAG3 6			
Engine Manufact Engine Model: Number of Cyline Cylinder Arrange	2 ders: ment: \	506A-E15TAG3 6 /ertical In Line			
Engine Manufact Engine Model: Number of Cyline Cylinder Arrange Cycle:	2 ders: ment: \ (in): 137.0 Turbo c	506A-E15TAG3 6 /ertical In Line 4 Stroke			
Engine Manufact Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	2. ders: ment: \ (in): 137.0 Turbo c	506A-E15TAG3 6 /ertical In Line 4 Stroke (5.4) / 171.0 (6.7) harged & air - to - air			

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	940.0	248.3	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCCB		

Performance	60	HZ	
Engine Speed:	1800		
Gross Engine Power:	kWm	Bhp	
Prime:	469.0	628.9	
Standby:	514.0	689.3	
Fuel Consumption:	L/Hr	US Gal/Hr	
Prime:	101	26.68	
Standby:	114	30.12	

Standard Reference Conditions:

Output ratings are presented at normal **c**onditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Wic	lth	Hei	ght		Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3871.0	152.4	1120.0	44.1	2130.0	83.9	3747.0	8260.0	3847.0	8481.0
						* With Lube	Dil	* With Lube Oil	& Coolant

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF

Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

Rating Definition

Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	60Hz		
		M³∕min	Ft³/min
Combustion Air Flow:		38.0	1342
Exhaust Gas Flow:		105.3	3719
Radiator Cooling: Air Flow		822.0	29028.7

*Cooling system designed to operate in high ambient conditions

Alternator Data				
Alternator Model:	Leroy Somer			
Alternator Manufacturer:	LSA47.2S5			
Insulation Class:	Single (1)			
Number of Bearings:	Н			
Wires:	12			
Total Harmonic Content:	<1.5%			
Excitation System:	IP 23			
Ingress Protection Rating:	Shunt			
Winding Pitch Code:	2/3 - 6			



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication 60Hz		
Liter	US/Gal	
58.0	15.3	
62.0	16.4	
°C	۴F	
590	1094	
	Liter 58.0 62.0 °C	



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories, all data is correct at the time of process and we reserve the right to change specification without prior notice

Distributed & Serviced by:



2704/2020

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com