



MP700E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output R	ating at -	50H	z		
400V	KVA		KW		
Prime 6	550.0		520.0		
Standby	700.0		560.0		
			@ 0.8 p.f.		
Generator Output Rating at - 60Hz					
480V	KVA		KW		
Prime 6	625.0		500.0		
Standby	687.0		550.0		
			@ 0.8 p.f.		
Engine Data					
Engine Data Engine Manufacturer:	P	erkin	s USA		
-	•		s USA 18TAG2		
Engine Manufacturer:	•		18TAG2		
Engine Manufacturer: Engine Model:	280	6A-E	18TAG2		
Engine Manufacturer: Engine Model: Number of Cylinders:	280	6A-E	18TAG2 In Line		
Engine Manufacturer: Engine Model: Number of Cylinders: Cylinder Arrangement:	280 Ver	6A-E 6 rtical 4 Str	18TAG2 In Line		
Engine Manufacturer: Engine Model: Number of Cylinders: Cylinder Arrangement: Cycle:	280 Ver 145.0 (! Turbo ch	6A-E frtical 4 Str 5.7) /	18TAG2 In Line oke		
Engine Manufacturer: Engine Model: Number of Cylinders: Cylinder Arrangement: Cycle: Bore/Stroke mm (in):	280 Ver 145.0 (! Turbo ch	6A-E frtical 4 Str 5.7) /	In Line oke 183.0 (7.2) d & air-to-air cooled		

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	1250.0	330.2		
Fuel Tank:	Powder Coated Steel			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Engine Speed: 1500 1800 Gross Engine Power: kWm Bhp kWm Bhp Prime: 584.0 783.1 567.7 761.3 Standby: 628.0 842.1 623.0 835.4
Prime: 584.0 783.1 567.7 761.3
56.10 7.6512 56717 7.6215
Standby: 628.0 842.1 623.0 835.4
Fuel Consumption: L/Hr us Gal/Hr L/Hr us Gal/Hr
Prime: 132 34.87 127 35.55
Standby: 143 37.78 141 37.25

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wi	dth	He	eight	I	Dry	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3919.0	154.3	1536.0	60.5	2229.0	87.8	4362.0	9616.6	4470.0	9854.7

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz
	M³/min Ft³/min	M³/min Ft³/min
Combustion Air Flow:	40.0 1413	45.0 1589
Exhaust Gas Flow:	114.0 4026	118.0 4167
Radiator Cooling: Air Flow	702.0 24791	852.0 30088

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

7	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 49.3 S4 TALO47F
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 4% < 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	61.0	16.1	61.0	16.1
Lube Oil Capacity:	62.0	16.4	62.0	16.4
	°C	°F	°C	°F
Exhaust Temperature:	553	1027	489	912



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



JAN2014 VER.1