



MP76-MP84E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 60Hz					
220/127V	KVA			KW	
Prime	76.0			61.0	
Standby	84.0			67.0	
				@ 0.8 p.f.	
Generator Out	out Ratin	g at - 6	0Hz		
380/220V	KVA			KW	
Prime	69.0			55.0	
Standby	76.0			61.0	
				@ 0.8 p.f.	
Engine Data					
Engine Manufact	urer:	Pei	rkins UI	<	
Engine Model:		1104A-44TG1			
Number of Cylind	ders:		4		
Cylinder Arrange	ment:	Vertical In Line			
Cycle:		4 Stroke			
Bore/Stroke mm	(in): 10	105.0 (4.1) / 127.0 (5.0)			
Induction:		Turbo charged			
Compression rati	o:	17.25:1			
Displacement / (c	ru.in):	4.4	4 (269)		

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	220.0	58.1	
Fuel Tank:	UV Resistant MDPE		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

Performance	60HZ		
Engine Speed:	1800		
Gross Engine Power:	kWm	Bhp	
Prime:	70.7	94.8	
Standby:	77.5	103.9	
Fuel Consumption:	L/Hr	US Gal/Hr	
Prime:	17.8	3.9	
Standby:	19.7	4.3	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wid	lth	He	ight	[Ory	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2200.0	86.6	746.0	29.4	1465.0	57.7	1023.0	2255.3	1050.0	2314.9

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	60Hz		
	M³/min	Ft³/min	
Combustion Air Flow:	5.5	194.2	
Exhaust Gas Flow:	14.3	504.9	
Radiator Cooling: Air Flow	111.0	3920	

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data Alternator Manufacturer: Leroy Somer **Alternator Model:** LSA44.3S2 **Number of Bearings:** Single (1) **Insulation Class:** Н **Total Harmonic Content:** <2% Wires: 12 **Ingress Protection Rating:** IP 23 **Excitation System:** Shunt Winding Pitch Code: 2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication60HzLiterUS/GalCoolant Capacity:13.13.46Lube Oil Capacity:8.02.11°C°FExhaust Temperature:535995



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories, all data is correct at the time of process and we reserve the right to change specification without prior notice

Distributed & Serviced by:



2304/2020